

SEMI SYNTHETIC 4T 10W40

DESCRIPTION

DashOil has developed a high-performance synthetic lubricant for bikers that aims to deliver the finest riding experience and engine performance. The lubricant provides excellent engine cleanliness, wear, and corrosion prevention. It promotes peak engine and gear performance, increases engine output, and stabilizes fuel consumption control. It is designed to provide worry-free engine and component protection.

STANDARD & SPECIFICATIONS

Surpasses JASO MA2 and API SP industry requirements.

SUITABILITY

Suitable for all 4-stroke long-ride motorcycles with either a carburetor or fuel injection system. Always adhere to the motorcycle manufacturer's instructions.

RECOMMENDATIONS

To ensure optimal performance and biking experience, do not combine with other synthetic or mineral lubricants. Oil changes depend on usage and bike type.

PROPERTIES & CHARACTERISTICS

NAME	METHOD	TYPICAL PROPERTIES
Density @ 15 °C (kg/L)	ASTM D4052	0.8720
Pour Point °C	ASTM D97	-25
Flash Point °C	ASTM D93	210
Viscosity @ 100 °C (cSt)	ASTM D7042	14.55
Viscosity @ 40 °C (cSt)	ASTM D7042	103.37
Viscosity Index	ASTM D2270	145.2

DASHOIL SEMI SYNTHETIC 4T 10W40
01 March 2023

We reserve the right to change our products' general characteristics to provide our clients with the most up-to-date technological advances. This data sheet is accurate as of the publication date but is not guaranteed to be complete. It is based on standard tests and should be evaluated for safety. Users are responsible for evaluating products, determining suitability, and complying with rules. TDC AUTOMOBILE SDN BHD and its subsidiaries accept no responsibility for any damage or harm caused by abnormal use or disobedience with recommendations.