

Product Data Sheet

GEAR OIL MINERAL 4AT 80W90

DESCRIPTION

DashOil developed the mineral gear oil, expertly crafted to maximize the performance and extend the lifespan of your scooter's transmission and differential systems. This advanced gear oil is formulated with premium quality, providing exceptional protection against wear, corrosion, and extreme pressure. Its superior viscosity guarantees smooth and efficient operation across various temperatures, reducing friction and boosting fuel efficiency.

STANDARD & SPECIFICATIONS

Surpasses API GL-4, API GL-5, MIL-L 2105 D industry requirements.

SUITABILITY

Suitable for all 4-stroke automatic scooter motorcycles. Always adhere to the motorcycle manufacturer's instructions.

RECOMMENDATIONS

To ensure optimal performance and biking experience, do not combine with other synthetic or mineral gear oil. Gear oil changes depend on usage and bike type.

PROPERTIES & CHARACTERISTICS

NAME	METHOD	TYPICAL PROPERTIES
Density @ 15 °C (kg/L)	ASTM D4052	0.8817
Flash Point °C	ASTM D93	210
Viscosity @ 100 °C (cSt)	ASTM D7042	15.8
Viscosity @ 40 °C (cSt)	ASTM D7042	141
Viscosity Index	ASTM D2270	117

DASHOIL 4AT GEAR OIL MINERAL 80W90 01 March 2023

We reserve the right to change our products' general characteristics to provide our clients with the most up-to-date technological advances. This data sheet is accurate as of the publication date but is not guaranteed to be complete. It is based on standard tests and should be evaluated for safety. Users are responsible for evaluating products, determining suitability, and complying with rules. TDC AUTOMOBILE SDN BHD and its subsidiaries accept no responsibility for any damage or harm caused by abnormal use or disobedience with recommendations.



202, Block B, Phileo Damansara 2, No. 15, Jalan 16/11, Off Jalan Damansara, 46350 Petaling Jaya, Selangor D. E., Malaysia.

