

### BP38 CHAIN LUBE

#### DESCRIPTION

This chain lube is designed to protect motorbike chains from rust and wear. It is designed to stick to the chain's surface and create a protective anti-wear film that will certainly increase the chain's lifespan. Its adhesive characteristics allow it to remain in place for extended periods of time, providing surface separating films without the need to reapply.

#### TYPICAL CHARACTERISTICS

| COMMERCIAL NAME          | METHOD     | CHARACTERISTICS |
|--------------------------|------------|-----------------|
| APPEARANCE BEFORE DRY    |            | THICK RED FLUID |
| APPEARANCE WHEN DRY      |            | MEDIUM SOFT WAX |
| VISCOSITY @ 100 °C (CST) | ASTM D7042 | 15.47           |
| VISCOSITY @ 40 °C (CST)  | ASTM D7042 | 94.57           |
| VISCOSITY INDEX          | ASTM D2270 | 174             |

#### ADVANTAGES

- Protection and lubrication for optimal power in harsh environments
- High performance at extreme temperatures and minimal friction
- Resistance to water "wash off"
- Protection against corrosion, rust and wear
- Adhesion to minimize fling

#### APPLICATION

Applicable for all motorcycle chain type (O-ring, X-ring, Z-ring).

DASHOIL BP38 CHAIN LUBE  
01 MARCH 2024

We reserve the right to change our products' general characteristics to provide our clients with the most up-to-date technological advances. This data sheet is accurate as of the publication date but is not guaranteed to be complete. It is based on standard tests and should be evaluated for safety. Users are responsible for evaluating products, determining suitability, and complying with rules. TDC AUTOMOBILE SDN BHD and its subsidiaries accept no responsibility for any damage or harm caused by abnormal use or disobedience with recommendations.