

### MINERAL 4T SAE40

#### DESCRIPTION

DashOil developed high-performance synthetic lubricants for bikers to improve their riding experience and engine performance. These lubricants are designed to provide worry-free protection to engine and component components, resulting in optimal engine and gear performance.

#### STANDARD & SPECIFICATIONS

Surpasses JASO MA2 and API SL industry requirements.

#### SUITABILITY

Suitable for all 4-stroke long-ride motorcycles with either a carburetor or fuel injection system. Always adhere to the motorcycle manufacturer's instructions.

#### RECOMMENDATIONS

To ensure optimal performance and biking experience, do not combine with other synthetic or mineral lubricants. Oil changes depend on usage and bike type.

#### PROPERTIES & CHARACTERISTICS

NAME	METHOD	TYPICAL PROPERTIES
Density @ 15 °C (kg/L)	ASTM D4052	0.8836
Pour Point °C	ASTM D97	-15
Flash Point °C	ASTM D93	205
Viscosity @ 100 °C (cSt)	ASTM D7042	14.11
Viscosity @ 40 °C (cSt)	ASTM D7042	126.25
Viscosity Index	ASTM D2270	110.4

DASHOIL MINERAL 4T SAE40  
01 March 2023

We reserve the right to change our products' general characteristics to provide our clients with the most up-to-date technological advances. This data sheet is accurate as of the publication date but is not guaranteed to be complete. It is based on standard tests and should be evaluated for safety. Users are responsible for evaluating products, determining suitability, and complying with rules. TDC AUTOMOBILE SDN BHD and its subsidiaries accept no responsibility for any damage or harm caused by abnormal use or disobedience with recommendations.