

H500 SYNTHETIC TECHNOLOGY 4T 15W50

DESCRIPTION

DashOil has developed a high-performance synthetic lubricant for bikers that prioritizes engine performance and cleanliness. The lubricant provides outstanding wear protection, corrosion resistance, thermal stability, corrosion inhibitors, clutch performance, and friction durability. It also offers stabilized fuel consumption control, delivering a smooth ride and optimal engine performance.

STANDARD & SPECIFICATIONS

Surpasses JASO MA2 and API SP industry requirements.

SUITABILITY

Suitable for all 4-stroke long-ride motorcycles with either a carburetor or fuel injection system. Always adhere to the motorcycle manufacturer's instructions.

RECOMMENDATIONS

To ensure optimal performance and biking experience, do not combine with other synthetic or mineral lubricants. Oil changes depend on usage and bike type.

PROPERTIES & CHARACTERISTICS

NAME	METHOD	TYPICAL PROPERTIES
Density @ 15 °C (kg/L)	ASTM D4052	0.8814
Pour Point °C	ASTM D97	-20
Flash Point °C	ASTM D93	210
Viscosity @ 100 °C (cSt)	ASTM D7042	17.85
Viscosity @ 40 °C (cSt)	ASTM D7042	149
Viscosity Index	ASTM D2270	132

DASHOIL H500 SYNTHETIC TECHNOLOGY 4T 15W50
01 March 2023

We reserve the right to change our products' general characteristics to provide our clients with the most up-to-date technological advances. This data sheet is accurate as of the publication date but is not guaranteed to be complete. It is based on standard tests and should be evaluated for safety. Users are responsible for evaluating products, determining suitability, and complying with rules. TDC AUTOMOBILE SDN BHD and its subsidiaries accept no responsibility for any damage or harm caused by abnormal use or disobedience with recommendations.